

Industrial Grade
SODIMM DDR5 5600 8GB
Datasheet
(SQR-SD5I8G5K6SNGPB)

CONTENTS

1. Description	4
2. Features.....	4
3. Dimension	5
4. Pin Descriptions	6
5. Pin Assignments	7
6. Block Diagram	8
7. Thermal Characteristics	9
8. IDD, IDDQ and IPP Specifications	10
9. Timing Parameters	11
10. SPD	12
Appendix: Part Number Table.....	17

Revision History

Rev	Date	Modification
1.0	26 th Feb., 2024	Official release

Advantech reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Advantech is believed to be accurate and reliable. However, Advantech does not assure any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

Copyright © 1983-2011 Advantech Co., Ltd. All rights reserved.

1. Description

WT DDR5 SODIMM							
Part Number	Density	DATA TRANSFER RATE	DIMM Organization	Number of DRAM	Number of rank	side	ECC
SQR-SD5I8G5K6SNGPB (Samsung 1Gx16 P-die)	8GB	5600 MT/s	1Gx64	4	1	1	N

2. Features

● Key Parameter

Industry Nomenclature	tCK (ns)	tRCD (ns)	tRP (ns)	tRAS (ns)	tRC (ns)
PC5-5600	0.357	16.00	16.00	32.00	48.00


Supported Data Transfer Rate				
Industry Nomenclature	CL=36	CL=40	CL=42	CL=46
PC5-5600	4400	4800	5200	5600

● tRFC parameter by Density

tRFC parameter by IC Configuration					
Parameter	IC Configuration				Unit
	8Gb	16Gb	24Gb	32Gb	
tRFC1,min	195	295	TBD	TBD	ns
tRFC2,min	130	160	TBD	TBD	ns
tRFCsb,min	115	130	TBD	TBD	ns

- JEDEC Standard 262-pin Small Outline Dual In-Line Memory Module
- VDD=VDDQ= 1.1V (1.067V ~ 1.166V)
- VPP=1.8V (1.746V ~ 1.908V)
- VDDSPD= 1.8V
- On-die, internal, adjustable VREF generation for DQ,CA,CS
- 16n-bit prefetch
- Two independent I/O sub channels
- Programmable /CAS Latency: 22,26,28,30,32,36,40,42,46,50
- tREFI 3.9us for -40°C ≤ Tcase < 85°C, tREFI 1.95us for 85°C < Tcase ≤ 95°C
- On-Die ECC
- PMIC on DIMM, nominal supply 5V/2A, VIN_Bulk input supply range: 4.25 V to 5.5 V
- Fly-by topology
- I3C/I2C support
- Terminated control and C/A bus
- SPD EEPROM Hub and Integrated Thermal Sensor
- Halogen-free

3. Dimension



Note: All dimensions are in millimeters (mils) and should be kept within a tolerance of ± 0.15 (6), unless otherwise specified.


4. Pin Descriptions

Symbol	Type	I/O Level	Description	Symbol	Type	I/O Level	Description
CK_t, CK_c	Input	VDDQ	Clock	DQ[31:0]_A DQ[31:0]_B	Input/ Output	VDDQ	Data Input/Output
CA[12:0]_A CA[12:0]_B	Input	VDDQ	Command/Address Inputs	CB[3:0]_A CB[3:0]_B	Input/ Output	VDDQ	ECC Check Bits Input/Output
CS[1:0]_A CS[1:0]_B	Input	VDDQ	Chip Select	DQS[4:0]_A_t DQS[4:0]_B_t	Input/ Output	VDDQ	Data Strobe
ALERT_n	Output	VDDQ	Alert	DQS[4:0]_A_c DQS[4:0]_B_c	Input/ Output	VDDQ	Data Strobe
RESET_n	CMOS Input	VDDQ	Active Low Asynchronous Reset	DM[3:0]_A_n DM[3:0]_B_n	Input	VDDQ	Input Data Mask
PWR_GOOD	Input/ Output	VDDQ	Power Good Indicator	VIN_BULK	Supply		External Power Supply
HSCL	Input	VOUT	Host Sideband Bus Clock	PWR_EN	Input		PMIC Enable
HSDA	Input/ Output	VOUT	Host Sideband Bus Data	VSS	Supply		Ground
HSA	Input	GND	Host Sideband Bus Device ID	RFU			Reserved for future use

5. Pin Assignments

262-Pin DDR5 SODIMM Front								262-Pin DDR5 SODIMM Back							
Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol
1	VIN_BULK	67	Vss	133	CK0_A_c	199	DQ8_B	2	HAS	68	DQ21_A	134	CK1_A_c	200	Vss
3	VIN_BULK	69	DQ22_A	135	Vss	201	Vss	4	HSCL	70	Vss	136	Vss	202	DQ9_B
5	RFU	71	Vss	137	CK0_B_t	203	DQ10_B	6	HSDA	72	DQ23_A	138	CK1_B_t	204	Vss
7	PWR_GOOD	73	DQ24_A	139	CK0_B_c	205	Vss	8	PWR_EN	74	Vss	140	CK1_B_c	206	DQ11_B
9	Vss	75	Vss	141	Vss	207	DQS1_B_c	10	Vss	76	DQ25_A	142	Vss	208	Vss
11	DQ0_A	77	DQ26_A	143	RFU	209	DQS1_B_t	12	DQ1_A	78	Vss	144	CA12_B	210	DM1_B_n
13	Vss	79	Vss	145	CA11_B	211	Vss	14	Vss	80	DQ27_A	146	CA10_B	212	Vss
15	DQ2_A	81	DQS3_A_c	147	Vss	213	DQ12_B	16	DQ3_A	82	Vss	148	Vss	214	DQ13_B
17	Vss	83	DQS3_A_t	149	CA9_B	215	Vss	18	Vss	84	DM3_A_n	150	CA8_B	216	Vss
19	DM0_A_n	85	Vss	151	CA7_B	217	DQ14_B	20	DQS0_A_c	86	Vss	152	CA6_B	218	DQ15_B
21	Vss	87	DQ28_A	153	Vss	219	Vss	22	DQS0_A_t	88	DQ29_A	154	Vss	220	Vss
23	DQ4_A	89	Vss	155	CA5_B	221	DQ16_B	24	Vss	90	Vss	156	CA4_B	222	DQ17_B
25	Vss	91	DQ30_A	157	CA3_B	223	Vss	26	DQ5_A	92	DQ31_A	158	CA2_B	224	Vss
27	DQ6_A	93	Vss	159	Vss	225	DQ18_B	28	Vss	94	Vss	160	Vss	226	DQ19_B
29	Vss	95	CB0_A	161	CS0_B_n	227	Vss	30	DQ7_A	96	CB1_A	162	CA1_B	228	Vss
31	DQ8_A	97	Vss	163	RESET_n	229	DM2_B_n	32	Vss	98	Vss	164	CA0_B	230	DQS2_B_c
33	Vss	99	CB2_A	165	CS1_B_n	231	Vss	34	DQ9_A	100	DQS4_A_c	166	Vss	232	DQS2_B_t
35	DQ10_A	101	Vss	167	Vss	233	DQ20_B	36	Vss	102	DQS4_A_t	168	CB0_B	234	Vss
37	Vss	103	CB3_A	169	DQS4_B_c	235	Vss	38	DQ11_A	104	Vss	170	Vss	236	DQ21_B
39	DQS1_A_c	105	Vss	171	DQS4_B_t	237	DQ22_B	40	Vss	106	CS0_A_n	172	CB1_B	238	Vss
41	DQS1_A_t	107	CA0_A	173	Vss	239	Vss	42	DM1_A_n	108	ALERT_n	174	Vss	240	DQ23_B
43	Vss	109	CA1_A	175	CB3_B	241	DQ24_B	44	Vss	110	CS1_A_n	176	CB2_B	242	Vss
45	DQ12_A	111	Vss	177	Vss	243	Vss	46	DQ13_A	112	Vss	178	Vss	244	DQ25_B
47	Vss	113	CA2_A	179	DQ0_B	245	DQ26_B	48	Vss	114	CA3_A	180	DQ1_B	246	Vss
49	DQ14_A	115	CA4_A	181	Vss	247	Vss	50	DQ15_A	116	CA5_A	182	Vss	248	DQ27_B
51	Vss	117	Vss	183	DQ2_B	249	DQS3_B_c	52	Vss	118	Vss	184	DQ3_B	250	Vss
53	DQ16_A	119	CA6_A	185	Vss	251	DQS3_B_t	54	DQ17_A	120	CA7_A	186	Vss	252	DM3_B_n
55	Vss	121	CA8_A	187	DM0_B_n	253	Vss	56	Vss	122	CA9_A	188	DQS0_B_c	254	Vss
57	DQ18_A	123	Vss	189	Vss	255	DQ28_B	58	DQ19_A	124	Vss	190	DQS0_B_t	256	DQ29_B
59	Vss	125	CA10_A	191	DQ4_B	257	Vss	60	Vss	126	CA11_A	192	Vss	258	Vss
61	DM2_A_n	127	CA12_A	193	Vss	259	DQ30_B	62	DQS2_A_c	128	RFU	194	DQ5_B	260	DQ31_B
63	Vss	129	Vss	195	DQ6_B	261	Vss	64	DQS2_A_t	130	Vss	196	Vss	262	Vss
65	DQ20_A	131	CK0_A_t	197	Vss			66	Vss	132	CK1_A_t	198	DQ7_B		

6. Block Diagram



7. Thermal Characteristics

Symbol	Parameter		Rating	Units	Note
T _c	Operation Temperature	Normal Operating Temp.	-40 to 85	°C	1,2,3
		Extended Temp.	85 to 95	°C	1,2,3,4
T _{STG}	Storage Temperature		-55 to 100	°C	5

Note:

1. Maximum operating case temperature; T_c is measured in the center of the package.
2. A thermal solution must be designed to ensure the DRAM device does not exceed the maximum T_c during operation.
3. Device functionality is not guaranteed if the DRAM device exceeds the maximum T_c during operation.
4. If T_c exceeds 85°C, the DRAM must be refreshed externally at 2X refresh, which is a 1.95μs interval refresh rate.
5. Storage temperature is defined as the temperature of the top/center of the DRAM and does not reflect the storage temperatures of shipping trays.

8. IDD, IDDQ and IPP Specifications

Symbol	Description	Value		Units
		IDD Max.	IPP Max.	
IDD0	Operating One Bank Active-Precharge Current	216	72	mA
IDD0F	Operating Four Bank Active-Precharge Current	480	112	mA
IDD2N	Precharge Standby Current	112	56	mA
IDD2P	Precharge Power-Down Current	268	56	mA
IDD3N	Active Standby Current	228	64	mA
IDD3P	Active Power-Down Current	132	64	mA
IDD4R	Operating Burst Read Current	1136	52	mA
IDD4W	Operating Burst Write Current	1388	40	mA
IDD5B	Burst Refresh Current (Normal Refresh Mode)	1028	324	mA
IDD5C	Burst Refresh Current (Same Bank Refresh Mode)	396	144	mA
IDD6N	Self Refresh Current: Normal Temperature Range	256	108	mA
IDD6E	Self Refresh Current: Extended Temperature Range	376	140	mA
IDD7	Operating Bank Interleave Read Current	1568	180	mA
IDD8	Maximum Power Saving Deep Power Down Current	80	56	mA

9. Timing Parameters

Parameter	Symbol	5600		6000		6400		Unit
		Min	Max	Min	Max	Min	Max	
Clock Timing								
Average clock period	tCK,AVG	0.357		0.333		0.312		ns
Command and Address Timing								
Read to Read command delay for same bank group	tCCD_L	8nCK,5ns (MAX)		8nCK,5ns (MAX)		8nCK,5ns (MAX)		nCK
WRITE to WRITE command delay for same bank group	tCCD_L_WR	32nCK, 20ns (MAX)		32nCK, 20ns (MAX)		32nCK, 20ns (MAX)		nCK
WRITE to WRITE command delay for same bank group, second WRITE not RMW	tCCD_L_WR2	16nCK, 10ns (MAX)		16nCK, 10ns (MAX)		16nCK, 10ns (MAX)		nCK
Read to Read or Write to Write command delay for different bank group for BL16, BC8 OTF	tCCD_S	8		8		8		nCK
ACTIVATE to ACTIVATE command delay to different bank group for 2KB page size	tRRD_S,2K	8		8		8		nCK
ACTIVATE to ACTIVATE command delay to different bank group for 1KB page size	tRRD_S,1K	8		8		8		nCK
ACTIVATE to ACTIVATE command delay to same bank group for 2KB page size	tRRD_L,2K	8nCK,5ns (MAX)		8nCK,5ns (MAX)		8nCK,5ns (MAX)		nCK
ACTIVATE to ACTIVATE command delay to same bank group for 1KB page size	tRRD_L,1K	8nCK,5ns (MAX)		8nCK,5ns (MAX)		8nCK,5ns (MAX)		nCK
Four activate window for 2KB page size	tFAW,2K	40nCK, 14.280ns (MAX)		40nCK, 13.333ns (MAX)		40nCK, 12.500ns (MAX)		ns
Four activate window for 1KB page size	tFAW,1K	32nCK, 11.428ns (MAX)		32nCK, 10.666ns (MAX)		32nCK, 10.000ns (MAX)		ns
Delay from start of internal WRITE transaction to internal READ command for different bank group	tWTR_S	2.5		2.5		2.5		ns
Delay from start of internal WRITE transaction to internal READ command for same bank group	tWTR_L	10		10		10		ns
Delay from start of internal WRITE transaction to internal READ with AUTO PRECHARGE command for same bank	tWTRA	tWR-tRTP		tWR-tRTP		tWR-tRTP		ns
Internal READ command to PRECHARGE command delay	tRTP	7.5		7.5		7.5		ns
PRECHARGE to PRECHARGE delay	tPPD	2		2		2		nCK
WRITE recovery time	tWR	30		30		30		ns

10. SPD

Byte Number	Function Described	Function supported	Hex Value
0	Number of Bytes in SPD Device	1024 Bytes	30
1	SPD Revision for Base Configuration Parameters	Revision 1.0	10
2	Key Byte / Host Bus Command Protocol Type	DDR5 SDRAM	12
3	Key Byte / Module Type	SODIMM	03
4	First SDRAM Density and Package	Monolithic 16Gb	04
5	First SDRAM Addressing	10 columns/16 rows	00
6	First SDRAM I/O Width	x16	40
7	First SDRAM Bank Groups & Banks Per Bank Group	4BGs / 4Banks per BG	42
8	Second SDRAM Density and Package	N/A	00
9	Second SDRAM Addressing	N/A	00
10	Second SDRAM I/O Width	N/A	00
11	Second SDRAM Bank Groups & Banks Per Bank Group	N/A	00
12	SDRAM BL32 & Post Package Repair	BL32 supported / sPPR	B0
13	SDRAM Duty Cycle Adjuster & Partial Array Self Refresh	PASR not supported	02
14	SDRAM Fault Handling	Yes	01
15	Reserved	Reserved	00
16	SDRAM Nominal Voltage, VDD	1.1V	00
17	SDRAM Nominal Voltage, VDDQ	1.1V	00
18	SDRAM Nominal Voltage, VPP	1.8V	00
19	SDRAM Timing	Standard	00
20	SDRAM Minimum Cycle Time ($t_{CKAVGmin}$), Least Significant Byte	357ps	65
21	SDRAM Minimum Cycle Time ($t_{CKAVGmin}$), Most Significant Byte	357ps	01
22	SDRAM Maximum Cycle Time ($t_{CKAVGmax}$), Least Significant Byte	1010ps	F2
23	SDRAM Maximum Cycle Time ($t_{CKAVGmax}$), Most Significant Byte	1010ps	03
24	CAS Latencies Supported, First Byte	22,26,28,30,32,36,40,42,46,50	7A
25	CAS Latencies Supported, Second Byte	22,26,28,30,32,36,40,42,46,50	AD
26	CAS Latencies Supported, Third Byte	22,26,28,30,32,36,40,42,46,50	00
27	CAS Latencies Supported, Fourth Byte	22,26,28,30,32,36,40,42,46,50	00
28	CAS Latencies Supported, Fifth Byte	22,26,28,30,32,36,40,42,46,50	00
29	Reserved	Reserved	00
30	SDRAM Minimum CAS Latency Time (t_{AAmin}), Least Significant Byte	16000ps	80
31	SDRAM Minimum CAS Latency Time (t_{AAmin}), Most Significant Byte	16000ps	3E
32	SDRAM Minimum RAS to CAS Delay Time (t_{RCDmin}), Least Significant Byte	16000ps	80
33	SDRAM Minimum RAS to CAS Delay Time (t_{RCDmin}), Most Significant Byte	16000ps	3E
34	SDRAM Minimum Row Precharge Delay Time (t_{RPmin}), Least Significant Byte	16000ps	80
35	SDRAM Minimum Row Precharge Delay Time (t_{RPmin}), Most Significant Byte	16000ps	3E
36	SDRAM Minimum Active to Precharge Delay Time (t_{RASmin}), Least Significant Byte	32000ps	00

37	SDRAM Minimum Active to Precharge Delay Time (t_{RASmin}), Most Significant Byte	32000ps	7D
38	SDRAM Minimum Active to Active/Refresh Delay Time (t_{RCmin}), Least Significant Byte	48000os	80
39	SDRAM Minimum Active to Active/Refresh Delay Time (t_{RCmin}), Most Significant Byte	48000os	BB
40	SDRAM Minimum Write Recovery Time (t_{WRmin}), Least Significant Byte	30000ps	30
41	SDRAM Minimum Write Recovery Time (t_{WRmin}), Most Significant Byte	30000ps	75
42	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFC1min}$, $t_{RFC1slr min}$), Least Significant Byte	295ns	27
43	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFC1min}$, $t_{RFC1slr min}$), Most Significant Byte	295ns	01
44	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFC2min}$, $t_{RFC2slr min}$), Least Significant Byte	160ns	A0
45	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFC2min}$, $t_{RFC2slr min}$), Most Significant Byte	160ns	00
46	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFCsbmin}$, $t_{RFCsbslr min}$), Least Significant Byte	130ns	82
47	SDRAM Minimum Refresh Recovery Delay Time ($t_{RFCsbdlr min}$), Most Significant Byte	130ns	00
48	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFC1dlr min}$), Least Significant Byte	N/A	00
49	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFC1dlr min}$), Most Significant Byte	N/A	00
50	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFC2dlr min}$), Least Significant Byte	N/A	00
51	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFC2dlr min}$), Most Significant Byte	N/A	00
52	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFCsbdlr min}$), Least Significant Byte	N/A	00
53	SDRAM Minimum Refresh Recovery Delay Time, 3DS Different Logical Rank ($t_{RFCsbdlr min}$), Most Significant Byte	N/A	00
54	SDRAM Refresh Management, First Byte, First SDRAM	N/A	00
55	SDRAM Refresh Management, Second Byte, First SDRAM	N/A	00
56	SDRAM Refresh Management, First Byte, Second SDRAM	N/A	00
57	SDRAM Refresh Management, Second Byte, Second SDRAM	N/A	00
58	SDRAM Adaptive Refresh Management Level A, First Byte, First SDRAM	N/A	00
59	SDRAM Adaptive Refresh Management Level A, Second Byte, First SDRAM	N/A	00
60	SDRAM Adaptive Refresh Management Level A, First Byte, Second SDRAM	N/A	00
61	SDRAM Adaptive Refresh Management Level A, Second Byte, Second SDRAM	N/A	00
62	SDRAM Adaptive Refresh Management Level B, First Byte, First SDRAM	N/A	00
63	SDRAM Adaptive Refresh Management Level B, Second Byte, First SDRAM	N/A	00
64	SDRAM Adaptive Refresh Management Level B, First Byte, Second SDRAM	N/A	00
65	SDRAM Adaptive Refresh Management Level B, Second Byte, Second SDRAM	N/A	00
66	SDRAM Adaptive Refresh Management Level C, First Byte, First SDRAM	N/A	00
67	SDRAM Adaptive Refresh Management Level C, Second Byte, First SDRAM	N/A	00
68	SDRAM Adaptive Refresh Management Level C, First Byte, Second SDRAM	N/A	00
69	SDRAM Adaptive Refresh Management Level C, Second Byte, Second SDRAM	N/A	00
70	SDRAM Minimum Active to Active Command Delay Time, Same Bank Group (t_{RRD_Lmin}), Least Significant Byte	5000ps	88
71	SDRAM Minimum Active to Active Command Delay Time, Same Bank Group (t_{RRD_Lmin}), Most Significant Byte	5000ps	13
72	SDRAM Minimum Active to Active Command Delay Time, Same Bank Group (t_{RRD_Lmin}), Lower Clock Limit	8nCK	08

73	SDRAM Minimum CAS_n to CAS_n Command Delay Time, Same Bank Group (tCCD_Lmin), Least Significant Byte	5000ps	88
74	SDRAM Minimum CAS_n to CAS_n Command Delay Time, Same Bank Group (tCCD_Lmin), Most Significant Byte	5000ps	13
75	SDRAM Minimum CAS_n to CAS_n Command Delay Time, Same Bank Group (tCCD_Lmin), Lower Clock Limit	8nCK	08
76	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Same Bank Group (tCCD_LWRmin), Least Significant Byte	20000ps	20
77	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Same Bank Group (tCCD_LWRmin), Most Significant Byte	20000ps	4E
78	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Same Bank Group (tCCD_LWRmin), Lower Clock Limit	32nCK	20
79	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Second Write not RMW, Same Bank Group (tCCD_LWR2min), Least Significant Byte	10000ps	10
80	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Second Write not RMW, Same Bank Group (tCCD_LWR2min), Most Significant Byte	10000ps	27
81	SDRAM Minimum Write CAS_n to Write CAS_n Command Delay Time, Second Write not RMW, Same Bank Group (tCCD_LWR2min), Lower Clock Limit	16nCK	10
82	SDRAM Minimum Four Activate Window (tFAWmin), Least Significant Byte	14285ps	CD
83	SDRAM Minimum Four Activate Window (tFAWmin), Most Significant Byte	14285ps	37
84	SDRAM Minimum Four Activate Window (tFAWmin), Lower Clock Limit	40nCK	28
85	SDRAM Minimum Internal Write to Read Command Delay Time, Same Bank Group, (tWTR_Lmin), Least Significant Byte	10000ps	10
86	SDRAM Minimum Internal Write to Read Command Delay Time, Same Bank Group, (tWTR_Lmin), Most Significant Byte	10000ps	27
87	SDRAM Minimum Internal Write to Read Command Delay Time, Same Bank Group, (tWTR_Lmin), Lower Clock Limit	16nCK	10
88	SDRAM Minimum Internal Write to Read Command Delay Time, Different Bank Group, (tWTR_Smin), Least Significant Byte	2500ps	C4
89	SDRAM Minimum Internal Write to Read Command Delay Time, Different Bank Group, (tWTR_Smin), Most Significant Byte	2500ps	09
90	SDRAM Minimum Internal Write to Read Command Delay Time, Different Bank Group, (tWTR_Smin), Lower Clock Limit	4nCK	04
91	SDRAM Minimum Internal Read to Precharge Command Delay Time, (tRTPmin), Least Significant Byte	7500ps	4C
92	SDRAM Minimum Internal Read to Precharge Command Delay Time, (tRTPmin), Most Significant Byte	7500ps	1D
93	SDRAM Minimum Internal Read to Precharge Command Delay Time, (tRTPmin), Lower Clock Limit	12nCK	0C
94~127	Reserved -- must be coded as 0x00	Reserved	00
128~191	Reserved for future use	Reserved	00
192	SPD Revision for SPD bytes 192~447	Revision 1.0	10
193	Hashing Sequence	No authentication	00
194	SPD Manufacturer ID Code, First Byte	Montage	86
195	SPD Manufacturer ID Code, Second Byte	Montage	32
196	SPD Device Type	Montage	80
197	SPD Device Revision Number	Montage	15
198	PMIC 0 Manufacturer ID Code, First Byte	Richtek	8A
199	PMIC 0 Manufacturer ID Code, Second Byte	Richtek	8C
200	PMIC 0 Device Type	Richtek	82
201	PMIC 0 Revision Number	Richtek	15
202	PMIC 1 Manufacturer ID Code, First Byte	N/A	00

203	PMIC 1 Manufacturer ID Code, Second Byte	N/A	00
204	PMIC 1 Device Type	N/A	00
205	PMIC 1 Revision Number	N/A	00
206	PMIC 2 Manufacturer ID Code, First Byte	N/A	00
207	PMIC 2 Manufacturer ID Code, Second Byte	N/A	00
208	PMIC 2 Device Type	N/A	00
209	PMIC 2 Revision Number	N/A	00
210	Thermal Sensor Manufacturer ID Code, First Byte	N/A	00
211	Thermal Sensor Manufacturer ID Code, Second Byte	N/A	00
212	Thermal Sensor Device Type	N/A	00
213	Thermal Sensor Revision Number	N/A	00
214	DRAM Specification Level	Reserved	00
215	SPD Specification Level	N/A	00
216	PMIC0 Specification Level	N/A	00
217	PMIC1 Specification Level	N/A	00
218	PMIC2 Specification Level	N/A	00
219	TS Specification Level	N/A	00
220	DIMM Specification Level	N/A	00
221~229	Reserved	Reserved	00
230	Module Nominal Height	29 < height <= 30 mm	0F
231	Module Maximum Thickness	1 < thickness <= 2 mm	01
232	Reference Raw Card Used	R/C C rev 0	02
233	DIMM Attributes	Tc -40 to +95 °C, 1row	31
234	Module Organization	Symmetrical 1 Package Rank	00
235	Memory Channel Bus Width	2 channels, 32 bits per channel	22
236~239	Reserved	Reserved	00
240~447	Reserved	Reserved	00
448~509	Reserved for future use	Reserved	00
510~511	CRC for SPD bytes 0~509	CRC	FA EA
512	Module Manufacturer ID Code, First Byte	Advantech	8A
513	Module Manufacturer ID Code, Second Byte	Advantech	C8
514	Module Manufacturing Location	Made in Taiwan	02
515~516	Module Manufacturing Date		-
517~520	Module Serial Number		-
521~550	Module Part Number	SQR-SD5I8G5K6SNGPB	53 51 52 2D 53 44 35 49 38 47 35 4B 36 53 4E 47 50 42 20 20 20 20 20 20 20 20 20 20 20 20
551	Module Revision Code		00
552	DRAM Manufacturer ID Code, First Byte	Samsung	80
553	DRAM Manufacturer ID Code, Second Byte	Samsung	CE

554	DRAM Stepping		00
555~639	Manufacturer's Specific Data		-
640~703	End User Programmable	Reserved	00
704~767	End User Programmable	Reserved	00
768~831	End User Programmable	Reserved	00
832~895	End User Programmable	Reserved	00
896~959	End User Programmable	Reserved	00
960~1023	End User Programmable	Reserved	00

Appendix: Part Number Table

Product	Advantech PN
SGRAM 8GB SO-DDR5-5600 1Gx16 Samsung (-40~95)	SQR-SD5I8G5K6SNGPB